

## Grip Range

Your attachment (name plate, cable tie mount, etc.) must fit between the head of the MetalTack and the surface of the base metal. The grip range may penetrate the base metal up to 0.010" (0.254mm).

## Point Length


Two sizes of point lengths are offered:

- 0.062" (1.574mm)
- 0.106" (2.692mm)

Use the larger point for increased withdrawal resistance and the smaller point in thin metals.

## Attachment Hole Range

The hole in your attachment must be greater than the shank diameter and less than the head diameter



Stocked



4-6 Week Lead Time  
50,000pcs Minimum

	Grip Range (Attachment Thickness)	Attachment Hole Range	Shank Diameter	Point Length	Part Number			
					Zinc Plated Carbon Steel	Nickel Plated Carbon Steel	Stainless Steel	Tool Steel
<b>3/16" Head Diameter</b>	0.010" - 0.020" (0.254 - 0.508mm)	0.109" - 0.156" (2.769 - 3.962mm)	0.104" (2.642mm)	0.106" (2.692mm)	<b>3158</b>	<b>3158N</b>	<b>3358</b>	<b>3458</b>
31 Series	0.020" - 0.030" (0.508 - 0.762mm)	0.109" - 0.156" (2.769 - 3.962mm)	0.104" (2.642mm)	0.106" (2.692mm)	<b>3170</b>	<b>3170N</b>	<b>3370</b>	<b>3470</b>
33 Series	0.020" - 0.030" (0.508 - 0.762mm)	0.109" - 0.156" (2.769 - 3.962mm)	0.104" (2.642mm)	0.106" (2.692mm)	<b>3161*</b>	<b>3161N</b>	<b>3361</b>	<b>3461</b>
34 Series	0.030" - 0.040" (0.762 - 1.016mm)	0.109" - 0.156" (2.769 - 3.962mm)	0.104" (2.642mm)	0.106" (2.692mm)	<b>3126</b>	<b>3126N</b>	<b>3326</b>	<b>3426</b>
Large Points	0.050" - 0.060" (1.270 - 1.524mm)	0.109" - 0.156" (2.769 - 3.962mm)	0.104" (2.642mm)	0.106" (2.692mm)	<b>3123</b>	<b>3123N</b>	<b>3323</b>	<b>3423</b>
	0.060" - 0.070" (1.524 - 1.778mm)	0.109" - 0.156" (2.769 - 3.962mm)	0.104" (2.642mm)	0.106" (2.692mm)	<b>3124</b>	<b>3124N</b>	<b>3324</b>	<b>3424</b>
Small Points	0.015" - 0.025" (0.381 - 0.635mm)	0.094" - 0.156" (2.388 - 3.962mm)	0.086" (2.184mm)	0.062" (1.575mm)	<b>3155</b>	<b>3155N</b>	<b>3355</b>	<b>3455</b>
	0.030" - 0.040" (0.381 - 0.635mm)	0.094" - 0.156" (2.388 - 3.962mm)	0.086" (2.184mm)	0.062" (1.575mm)	<b>3105</b>	<b>3105N</b>	<b>3305</b>	<b>3405</b>
<b>1/4" Head Diameter</b>	0.015" - 0.025" (0.381 - 0.635mm)	0.125" - 0.219" (3.175 - 5.563mm)	0.100" - 0.138" (2.540 - 3.505mm)	0.106" (2.692mm)	<b>4164</b>	<b>4164N</b>	<b>4364</b>	
41 Series**	0.020" - 0.030" (0.508 - 0.762mm)	0.187" - 0.219" (4.750 - 5.563mm)	0.154" - 0.195" (3.912 - 4.953mm)	0.106" (2.692mm)	<b>4136</b>	<b>4136N</b>	<b>4336</b>	
43 Series**	0.030" - 0.040" (0.762 - 1.016mm)	0.157" - 0.219" (3.988 - 5.563mm)	0.111" - 0.157" (2.819 - 3.988mm)	0.106" (2.692mm)	<b>4139</b>	<b>4139N</b>	<b>4339</b>	
Large Points	0.050" - 0.060" (1.270 - 1.524mm)	0.187" - 0.219" (4.750 - 5.563mm)	0.135" - 0.194" (3.429 - 4.928mm)	0.106" (2.692mm)	<b>4156</b>	<b>4156N</b>	<b>4356</b>	
	0.060" - 0.070" (1.524 - 1.778mm)	0.187" - 0.219" (4.750 - 5.563mm)	0.119" - 0.184" (3.023 - 4.674mm)	0.106" (2.692mm)	<b>4148</b>	<b>4148N</b>	<b>4348</b>	
	0.085" - 0.095" (2.159 - 2.413mm)	0.187" - 0.219" (4.750 - 5.563mm)	0.104" - 0.181" (2.642 - 4.597mm)	0.106" (2.692mm)	<b>4192</b>	<b>4192N</b>	<b>4392</b>	
	0.115" - 0.125" (2.921 - 3.175mm)	0.203" - 0.219" (5.156 - 5.563mm)	0.104" - 0.198" (2.642 - 5.029mm)	0.106" (2.692mm)	<b>4106</b>	<b>4106N</b>	<b>4306</b>	
<b>5/32" Head Diameter</b>	0.001" - 0.010" (0.025 - 0.254mm)	0.109" - 0.125" (2.769 - 3.175mm)	0.104" (2.642mm)	0.106" (2.692mm)	<b>5101</b>	<b>5101N</b>		
51 Series	0.010" - 0.020" (0.254 - 0.508mm)	0.109" - 0.125" (2.769 - 3.175mm)	0.109" (2.769mm)	0.106" (2.692mm)	<b>5158</b>	<b>5158N</b>		
Large Points	0.030" - 0.040" (0.762 - 1.016mm)	0.109" - 0.125" (2.769 - 3.175mm)	0.109" (2.769mm)	0.106" (2.692mm)	<b>5126</b>	<b>5126N</b>		

\* Part # 3161 has a beveled head edge

\*\* All 41 Series and 43 Series MetalTacks have tapered shanks



ISO 9001 Certified  
Made in the U.S.A.  
An Employee Owned Company

97 Dexter Rd, E. Providence, RI 02914  
Email: gripnail@gripnail.com  
Tel:(401) 216-7900 Fax:(401) 438-8520

